

MOTOR GUARD

BACK-UP PADS

NEW FROM MOTOR GUARD

HIGHEST QUALITY U.S. MANUFACTURED
FOR THE ULTIMATE REFINISHING TECHNOLOGY



Motor Guard Corporation is pleased to introduce a full line of Back-up Pad Products for automotive refinishing. Two sizes of molded urethane pads are offered in a variety of hardnesses and facings. These pads feature heavy-duty riveted hubs and are precision balanced for vibration free, flawless sanding. A soft, foam Interface Pad can be added to the 6" Back-up Pad for fine finish sanding and for full contact on irregular surfaces. Other accessories include a stiff, reinforced composite Backing Plate for aggressive sanding and grinding. Completing the line is a versatile Buffering Pad Holder for both

lambswool bonnets and foam polishing pads. A hook facing provides a slip-free hold while allowing for quick change of pads.

From Pulling to Painting, Motor Guard Corporation has a product for all of your autobody repair and refinishing needs.

Exclusive Features:

- Full Product Line to Meet All Your Shop Needs
- Highest Quality U.S. Manufactured Products
- Precision Controlled Weight and Balance for Vibration Free Operation
- Ultra Flat Faces for Flawless Sanding
- Innovative Facing Materials Provide Maximum Hold While Allowing for Quick Change of Abrasive Discs











MOTOR GUARD CORPORATION

MANTECA, CALIFORNIA • (209) 239-9191 • FAX (209) 239-5114 • www.motorguard.com

Printed in U.S.A. S1199

SELECTION CHART

	MODEL	DESCRIPTION	PURPOSE	SPECIFICATIONS
	BP-1016	MEDIUM BACK-UP PAD 6" FACE DIAMETER REGULAR PROFILE PSA FACE	MEDIUM EDGE PAD FOR PSA BACKED DISCS. FIRM ENOUGH FOR FLAT SURFACES YET SOFT ENOUGH FOR CURVED SURFACES.	DIAMETER: 6" FACE: VINYL HARDNESS: MEDIUM THREAD: 5/16-24 MALE MAX. RPM: 10,000
	BP-1116	FIRM BACK-UP PAD 6" FACE DIAMETER LOW PROFILE PSA FACE	FIRM, LOW PROFILE PAD FOR PSA BACKED DISCS. PROVIDES MAXIMUM FLATNESS.	DIAMETER: 6" FACE: VINYL HARDNESS: FIRM THREAD: 5/16-24 MALE MAX. RPM: 10,000
	BP-1026	MEDIUM BACK-UP PAD 6" FACE DIAMETER REGULAR PROFILE HOOK FACE	MEDIUM EDGE PAD FOR LOOP BACKED DISCS. FIRM ENOUGH FOR FLAT SURFACES YET SOFT ENOUGH FOR CURVED SURFACES.	DIAMETER: 6" FACE: HOOK HARDNESS: MEDIUM THREAD: 5/16-24 MALE MAX. RPM: 10,000
	BP-1126	FIRMBACK-UP PAD 6" FACE DIAMETER LOW PROFILE HOOK FACE	FIRM, LOW PROFILE PAD FOR LOOP BACKED DISCS. PROVIDES MAXIMUM FLATNESS.	DIAMETER: 6" FACE: HOOK HARDNESS: FIRM THREAD: 5/16-24 MALE MAX. RPM: 10,000
	BP-4005	BACKING PLATE REGULAR PROFILE	REINFORCED COMPOSITE PLATE PROVIDES A STRONG, STIFF BACKING FOR AGGRESSIVE SANDING AND GRINDING.	DIAMETER: 5" THICKNESS: .064" CENTER HOLE: 7/8" MAX. RPM: 6,000
	BP-1018	8" BACK-UP PAD REGULAR PROFILE	LARGE DIAMETER MEDIUM EDGE PAD FOR PSA BACKED DISCS. FIRM ENOUGH FOR FLAT SURFACES YET SOFT ENOUGH FOR CURVED SURFACES.	DIAMETER: 8" FACE: VINYL HARDNESS: MEDIUM THREAD: 5/8-11 FEMALE
	BP-2027	7" BUFFING PAD HOLDER	BUFFING AND POLISHING PAD HOLDER FOR LAMBSWOOL BONNETS AND FOAM POLISHING PADS.	DIAMETER: 7" FACE: HOOK THREAD: 5/8-11 FEMALE MAX. RPM: 2,000
	BP-3026	6" FOAM INTERFACE PAD HOOK FRONT LOOP BACK	SOFT FOAM INTERFACE PAD FOR USE ON 6" HOOK FACED DISCS. FOR FINE FINISH SANDING AND FULL CONTACT ON IRREGULAR SURFACES.	DIAMETER: 6" FACE: HOOK/LOOP HARDNESS: SOFT

SANDING GUIDE

HARDNESS	APPLICATION
FIRM	Firm Pads are designed for use on Flat Surfaces and with Abrasive Grits of 100 or Lower
MEDIUM	Medium Pads are designed for use on Flat or Curved Surfaces and with Abrasive Grits from 120 to 240
SOFT	Soft Pads are for designed use on Curved or Irregular Surfaces for Fine Finish Sanding with Abrasive Grits of 240 and Higher